DYMAXINC

BUILT TO LAST.

CONTRACTOR TREE SHEAR - EXCAVATOR

OVERVIEW

The **Dymax Contractor Series Tree Shear** is ideal for maintaining ditches around highways and county roads, as well as other utility clearing operations. Based upon the popular skid loader model The Dymax Contractor Series Tree Shear is available in either 14 or 16 inch cutting capacities. Each model features a single grapple cylinder and dual grapple arms to secure the tree prior to cutting. Equipped with reinforced welded tower with heavy duty grapples and integrated bolt on machine adapter providing adaptability to a wide range of excavators.

Model No.	Description	Max Cut Capacity Diameter	MIN/MAX-Excavator Size	Weight (kg) with Excavator adapter installed
DX-TS-FG-CS14in-HX-12T	Tree Shear - Grapple - Contractor Series 14 inch capacity - Hydraulic Excavator -	14 inch	14t-21t	1095
DX-TS-FG-CS16in-HX-14T 7021D	Tree Shear - Grapple - Contractor Series 16 inch capacity - Hydraulic Excavator -	16 inch	16t-22t	1180

Standard Features: Tube Frame • 3/4" AR400 cutting knives • 5.0x10 cylinders • Twin shear arms with dual grapples • chromed plated pivot pins and bushings, • Tube Frame • Bolt 303 excavator head plate with adapter and pins.

Hydraulic Requirements: Shear/Grapple, Type Two Way, GPM (min/max) 15-25, PSI (max) 3,500
Includes set of hose lines to machine lines. Disconnects to machine lines are not provided.

Specifications are subject to change without notice.

DYMAX

Practicality Brown Ltd
SL09LA United KIngdom

UK Distributor +44(0)1295690011

www.treeshears.co.uk
sales@treeshears.co.uk